

Letter of Compliance

Product: 1/2" thru 2" Maxline

Description: Semi-flexible compressed air piping system

Technical Specifications: Compressed air, vacuum, and inert gas applications
200 psi maximum working pressure at 23°C
160 psi maximum working pressure at 60°C
Temp range -40°C to 60°C
Compatible with common compressor lubricants

General Ratings: ASTM F1282
ASTM F1974
Compliant to Occupational Safety & Health Administration (OSHA)

Tubing Specifications: Material: inner and outer layer HDPE, center layer Aluminum
Blue color exterior, white interior, compressed air 1/2" – 2"
Green color exterior, white interior, inert gas 1/2" – 1"
Trade size callout measured with I.D.



Trade Size Callout Measured with O.D.

1/2" size	16 O.D. x 12.7 I.D.	100mm Min bend radius
3/4" size	25 O.D. x 20.3 I.D.	205mm Min bend radius
1" size	32 O.D. x 26 I.D.	250mm Min bend radius

Life Expectancy: 50 years



Fitting Specifications 1/2" – 1":

Compression Style
Body: nickel plated brass
Bite Ring: nickel plated brass
O-Ring: nitrile



Fitting Specifications 2":

Compression Style
Body: nickel plated brass
Bite Ring: stainless steel
O-Ring: nitrile



PRODUCTS MANUFACTURED BY THE SELLER CARRY A LIMITED ONE YEAR WARRANTY

Manufactured by RapidAir Products | www.rapidairproducts.com
6111 Mill Creek Drive Auburndale, WI 54412 | 800-954-3310
Australasian Distributor Rapidair Systems, Burpengary East, Qld 4505 Australia